

Drill-Hole	Target Area	UTM-E (m)	UTM-N (m)	Elevation (m)	Azimuth (°)	Dip (°)	Total Length (m)	Intersection		Core Length (m)	Au g/t	Ag g/t	Cu %	Lithology	
								From (m)	To (m)						
SST-06	Sub-Sill	422510.92	1989858.05	1158.38	90	-72	150.00		68.15	71.06	2.9	33.7	12.1	0.3	Skarn
SST-07	Sub-Sill	422453.12	1989886.99	1173.58	0	-90	317.80		140.78	148.13	7.4	23.0	31.9	1.2	Skarn
									256.76	272.80	16.0	19.4	28.2	1.0	Skarn
SST-08	Sub-Sill	422509.53	1989858.06	1158.42	0	-90	221.70		67.22	71.35	4.1	10.3	50.5	2.3	Skarn
									83.05	92.45	9.4	5.5	30.0	1.1	Skarn
									140.89	143.36	2.5	18.9	33.6	1.2	Skarn
SST-09	Sub-Sill	422385.11	1989765.80	1138.58	80	-81	200.50		91.71	97.80	6.1	14.7	3.7	0.2	Skarn
									118.39	122.50	4.1	23.2	25.6	1.2	Skarn
									139.90	146.67	6.7	6.7	14.4	0.6	Skarn
SST-10	Sub-Sill	422406.57	1989800.12	1143.41	90	-68	120.00		64.50	80.00	15.5	14.9	2.4	0.0	Skarn
									93.25	96.22	3.0	11.1	3.7	0.1	Skarn
SST-11	Sub-Sill	422517.59	1989840.11	1150.91	95	-65	101.20		98.38	99.91	1.5	3.5	8.8	0.2	Skarn
SST-15	Sub-Sill	422399.22	1989845.46	1175.20	95	-71	150.00		114.65	120.45	5.8	23.9	4.2	0.1	Skarn
									134.58	138.49	3.9	112.7	39.2	1.3	Skarn
SST-16	Sub-Sill	422348.54	1989829.52	1193.58	275	-85	314.60	No Intercepts							
SST-17	Sub-Sill	422555.27	1989831.73	1154.92	95	-60	101.50		80.04	81.36	1.3	16.3	27.2	0.9	Skarn
SST-31	Sub-Sill	422331.27	1989725.14	1128.79	130	-70	300.00		134.03	136.32	2.3	9.4	8.6	0.3	Skarn
SST-36	Sub-Sill	422395.47	1989863.16	1185.09	0	-90	302.50		274.53	285.12	10.6	9.1	36.2	3.4	Skarn

Notes:

True thickness of the mineralized zone is unknown and is reported as drill hole length

The gold values used to calculate the intercept composite are uncapped