

Table 1: Composite Weighted Average Assay Intervals, Farley Lake Project, 2015 Feasibility Drilling

HOLE-ID	FROM (m)	TO (m)	LENGTH (m)	Au (g/t)	SAMPLE	Wt. Avg. Au (g/t)	Interval (m)
FL15-01	40.37	40.90	0.53	0.41	775022		
FL15-01	89.00	90.50	1.50	11.50	775072		
FL15-02				No Data			
HOLE-ID	FROM (m)	TO (m)	LENGTH (m)	Au (g/t)	SAMPLE	Wt. Avg. Au (g/t)	Interval (m)
FL15-03				NSR			
FL15-04	28.26	29.00	0.74	16.05	777517		
FL15-04	79.80	80.30	0.50	1.78	777561		
FL15-05	117.50	118.50	1.00	2.39	775338		
FL15-05	186.00	187.00	1.00	1.97	775414		
FL15-05	207.60	208.20	0.60	3.43	775437	<b>1.07</b>	<b>2.40</b>
	208.20	209.00	0.80	0.04	775438		
	209.00	210.00	1.00	0.48	775439		
FL15-06	30.50	31.50	1.00	0.49	777617		
FL15-07				NSR			
FL15-08	44.65	45.65	1.00	3.00	777687	<b>2.17</b>	<b>1.55</b>
	45.65	46.20	0.55	0.66	777688		
FL15-08	116.10	117.10	1.00	0.88	777764		
FL15-09	19.95	20.85	0.90	0.84	775522		
FL15-09	26.85	27.85	1.00	0.49	775530	<b>0.48</b>	<b>2.95</b>
	27.90	28.85	0.95	0.47	775531		
	28.85	29.85	1.00	0.48	775532		
FL15-09	44.20	45.20	1.00	1.09	775546		
FL15-09	71.00	72.24	1.24	0.83	775574		

FL15-09	103.96	104.96	1.00	22.60	775609	<b>8.18</b>	<b>2.82</b>
	104.96	106.00	1.04	0.16	775610		
	106.00	106.78	0.78	0.39	775611		
FL15-09	137.74	138.74	1.00	1.47	775646	<b>1.97</b>	<b>5.26</b>
	138.74	139.74	1.00	2.46	775647		
	139.74	140.74	1.00	4.94	775648		
	140.74	141.74	1.00	0.37	775649		
	141.74	143.00	1.26	0.91	775650		

HOLE-ID	FROM (m)	TO (m)	LENGTH (m)	Au (g/t)	SAMPLE	Wt. Avg. Au (g/t)	Interval (m)
FL15-10	30.50	31.40	0.90	1.26	777826	<b>2.44</b>	<b>2.90</b>
	31.40	32.40	1.00	5.55	777827		
	32.40	33.40	1.00	0.40	777828		
FL15-11	25.00	26.00	1.00	2.97	777868		
FL15-11	30.00	31.00	1.00	4.50	777873		
FL15-12	34.20	35.00	0.80	0.46	775676		
FL15-13	54.40	54.90	0.50	3.77	777961		
FL15-13	91.30	92.00	0.70	2.06	778001		
FL15-14	100.00	101.00	1.00	15.20	775814		
FL15-14	109.00	110.00	1.00	0.79	775827		
FL15-14	118.00	119.00	1.00	3.52	775837		
FL15-14	130.00	131.00	1.00	0.42	775850		
FL15-14	150.00	151.00	1.00	1.85	775871		
FL15-14	177.00	178.00	1.00	0.41	775902		
FL15-14	184.50	185.00	0.50	4.99	775910	<b>4.90</b>	<b>5.50</b>
	185.00	186.10	1.10	1.19	775911		
	186.10	187.00	0.90	0.32	775912		
	187.00	187.50	0.50	3.78	775913		
	187.50	188.00	0.50	3.73	775914		
	188.00	189.00	1.00	0.21	775915		

	189.00	189.50	0.50	35.40	775916		
	189.50	190.00	0.50	2.36	775918		
FL15-15	19.00	20.00	1.00	0.42	775930		
	42.50	43.00	0.50	3.17	775955		
	156.00	156.50	0.50	0.48	776083		
	156.50	157.00	0.50	0.51	776084		
FL15-16	72.70	73.50	0.80	2.84	778068		
FL15-16	132.50	133.00	0.50	0.88	778135		
FL15-16	134.50	135.45	0.95	0.41	778138		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-16	137.40	138.40	1.00	0.68	778142		
FL15-16	158.00	158.50	0.50	0.44	778166		
FL15-17	70.00	71.00	1.00	8.66	778705		
FL15-17	74.00	75.00	1.00	3.32	778709		
FL15-17	81.00	82.00	1.00	0.91	778716		
FL15-17	88.00	89.00	1.00	2.34	778724		
FL15-17	91.00	92.00	1.00	0.84	778728		
FL15-17	139.00	140.00	1.00	0.52	778780		
FL15-18	39.45	40.10	0.65	0.50	776135		
FL15-18	44.35	45.40	1.05	2.38	776142		
FL15-18	49.40	50.20	0.80	0.86	776147		
FL15-18	90.00	91.00	1.00	26.80	776191		
FL15-19	36.00	37.00	1.00	4.42	778810	<b>11.70</b>	<b>10.60</b>
	37.00	38.00	1.00	19.15	778811		
	38.00	39.00	1.00	10.85	778812		
	39.00	39.80	0.80	10.20	778813		
	39.80	40.40	0.60	12.60	778814		
	40.40	41.00	0.60	9.13	778815		
	41.00	41.50	0.50	17.50	778816		
	41.50	42.00	0.50	7.71	778817		
	42.00	43.00	1.00	10.35	778818		

	43.00	43.50	0.50	8.29	778819		
	43.50	44.00	0.50	13.70	778821		
	44.00	44.50	0.50	18.70	778822		
	44.50	45.30	0.80	13.65	778823		
	45.30	46.00	0.70	17.55	778824		
	46.00	46.60	0.60	3.09	778826		
FL15-19	97.00	98.00	1.00	0.90	778882	<b>0.69</b>	<b>3.00</b>
	98.00	99.00	1.00	0.40	778883		
	99.00	100.00	1.00	0.77	778884		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-20A	49.00	50.00	1.00	0.61	776264		
FL15-20A	88.00	89.00	1.00	1.21	776306	<b>2.56</b>	<b>3.00</b>
	89.00	90.00	1.00	5.23	776307		
	90.00	91.00	1.00	1.24	776309		
FL15-20A	101.05	101.55	0.50	6.72	776321		
FL15-21	8.10	9.00	0.90	0.41	778233	<b>3.87</b>	<b>4.00</b>
	9.00	9.60	0.60	1.32	778234		
	9.60	10.20	0.60	3.47	778235		
	10.20	10.80	0.60	11.80	778236		
	10.80	11.60	0.80	0.21	778237		
	11.60	12.10	0.50	9.94	778238		
FL15-21	42.00	43.00	1.00	0.91	778274		
FL15-21	50.50	51.08	0.58	0.47	778285		
FL15-21	59.80	60.30	0.50	5.45	778295	<b>4.85</b>	<b>4.20</b>
	60.30	60.80	0.50	2.89	778296		
	60.80	61.40	0.60	9.43	778297		
	61.40	62.00	0.60	7.40	778298		
	62.00	63.00	1.00	2.25	778299		
	63.00	64.00	1.00	3.85	778301		
	65.75	66.75	1.00	4.80	778304		
FL15-21	69.75	70.75	1.00	0.44	778308	<b>3.22</b>	<b>9.35</b>

	70.75	71.75	1.00	3.50	778309		
	71.75	72.75	1.00	0.09	778310		
	72.75	73.75	1.00	0.84	778311		
	73.75	74.30	0.55	0.03	778312		
	74.30	75.30	1.00	1.45	778313		
	75.30	76.30	1.00	2.48	778314		
	76.30	77.10	0.80	0.07	778315		
	77.10	78.10	1.00	2.48	778316		
	78.10	79.10	1.00	18.75	778317		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-21	104.00	105.00	1.00	3.81	778346	<b>1.55</b>	<b>4.00</b>
	105.00	106.00	1.00	1.63	778347		
	106.00	107.00	1.00	0.24	778348		
	107.00	108.00	1.00	0.50	778349		
FL15-21	116.00	117.00	1.00	0.55	778358		
FL15-21	121.50	122.50	1.00	0.81	778364		
FL15-21	131.00	132.00	1.00	0.40	778373		
FL15-21	166.30	167.30	1.00	3.16	778411		
FL15-21	173.00	174.00	1.00	0.44	778418	<b>1.06</b>	<b>2.00</b>
	174.00	175.00	1.00	1.68	778419		
FL15-21	182.00	183.00	1.00	0.51	778429	<b>5.54</b>	<b>4.60</b>
	183.00	183.70	0.70	0.01	778430		
	183.70	184.40	0.70	0.01	778431		
	184.40	184.90	0.50	15.15	778432		
	184.90	185.40	0.50	0.10	778433		
	185.40	186.10	0.70	7.38	778434		
	186.10	186.60	0.50	24.30	778435		
FL15-21	194.00	195.00	1.00	0.63	778445		
FL15-22	35.00	36.00	1.00	0.59	778909		
FL15-22	41.00	42.00	1.00	2.06	778915	<b>3.40</b>	<b>2.08</b>
	42.00	43.08	1.08	4.64	778916		

FL15-22	54.00	54.60	0.60	3.29	778931		
FL15-23	44.30	45.00	0.70	2.53	779022	<b>4.61</b>	<b>6.10</b>
	45.00	46.10	1.10	1.00	779023		
	46.10	47.10	1.00	9.98	779024		
	47.60	48.00	0.40	5.35	779026		
	48.00	48.90	0.90	5.25	779027		
	48.90	49.80	0.90	6.71	779028		
49.80	50.90	1.10	2.16	779029			
FL15-23	72.20	73.40	1.20	0.83	779048		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-24				NSR			
FL15-25	30.00	31.00	1.00	9.51	778461	<b>5.30</b>	<b>3.30</b>
	31.00	32.00	1.00	3.42	778462		
	32.00	32.60	0.60	3.91	778463		
	32.60	33.30	0.70	3.17	778464		
FL15-25	49.00	50.00	1.00	1.31	778483		
FL15-25	86.00	87.10	1.10	0.89	778518		
FL15-25	114.90	115.90	1.00	3.27	778546		
FL15-26	31.50	32.30	0.80	0.71	776338	<b>0.55</b>	<b>1.80</b>
	32.30	33.30	1.00	0.42	776339		
FL15-26	73.00	74.00	1.00	1.03	776783	<b>6.34</b>	<b>2.00</b>
	74.00	75.00	1.00	11.80	776784		
	75.00	76.00	1.00	0.87	776785		
FL15-26	79.00	80.00	1.00	0.47	776789	<b>3.43</b>	<b>2.00</b>
	80.00	81.00	1.00	1.59	776790		
	81.00	82.00	1.00	5.26	776791		
FL15-27	87.00	87.95	0.95	1.83	779268	<b>9.36</b>	<b>2.75</b>
	87.95	88.75	0.80	29.40	779269		
	88.75	89.75	1.00	0.49	779270		
FL15-28				NSR			
FL15-29	14.00	15.25	1.25	1.04	776354		

FL15-29	17.50	18.20	0.70	2.75	776357		
FL15-29	21.20	22.20	1.00	0.85	776362	<b>0.94</b>	<b>8.00</b>
	22.20	23.20	1.00	0.65	776363		
	23.20	24.20	1.00	0.80	776364		
	24.20	25.20	1.00	0.16	776365		
	25.20	26.20	1.00	1.19	776366		
	26.20	27.20	1.00	1.62	776367		
	27.20	28.20	1.00	1.73	776368		
	28.20	29.20	1.00	0.48	776369		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-30	106.20	107.20	1.00	0.74	778639		
FL15-30	141.80	142.40	0.60	0.56	778674	<b>8.71</b>	<b>1.70</b>
	149.00	149.90	0.90	3.88	778685		
	149.90	150.70	0.80	14.15	778686		
FL15-31				NSR			
FL15-32				NSR			
FL15-33	47.00	47.80	0.80	0.96	714293	<b>2.06</b>	<b>2.00</b>
	47.80	48.30	0.50	5.93	714294		
	48.30	49.00	0.70	0.55	714295		
FL15-33	52.20	52.70	0.50	5.81	714299		
FL15-33	64.00	65.00	1.00	0.47	714312		
FL15-33	70.00	71.00	1.00	3.33	714318		
FL15-33	73.20	74.00	0.80	0.62	714322		
FL15-33	75.00	75.50	0.50	0.86	714324		
FL15-33	89.00	90.00	1.00	0.61	714341		
	90.00	91.00	1.00	2.35	714342		
	94.00	94.50	0.50	4.34	714346		
FL15-33	100.50	101.50	1.00	0.40	714353	<b>4.26</b>	<b>12.00</b>
	101.50	102.50	1.00	0.82	714354		
	102.50	103.50	1.00	0.32	714355		
	103.50	104.50	1.00	0.52	714356		

	104.50	105.50	1.00	1.14	714357		
	105.50	106.20	0.70	3.48	714358		
	106.20	106.80	0.60	11.70	714359		
	106.80	107.60	0.80	4.85	714361		
	107.60	108.30	0.70	2.58	714362		
	108.30	109.00	0.70	35.10	714363		
	109.00	109.90	0.90	2.22	714364		
	109.90	110.40	0.50	0.33	714365		
	110.40	111.00	0.60	2.65	714366		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-33 Cont'd	111.00	111.80	0.80	0.49	714367		
	111.80	112.50	0.70	5.84	714368		
FL15-33	116.50	117.50	1.00	1.07	714373	<b>2.95</b>	<b>8.20</b>
	117.50	118.50	1.00	0.18	714374		
	118.50	119.20	0.70	4.36	714376		
	119.20	119.80	0.60	4.06	714377		
	119.80	120.80	1.00	0.88	714378		
	120.80	121.60	0.80	0.60	714379		
	121.60	122.50	0.90	0.54	714381		
	122.50	123.10	0.60	4.01	714382		
	123.10	123.70	0.60	18.80	714383		
123.70	124.70	1.00	1.92	714384			
FL15-33	128.40	129.40	1.00	5.51	714389	<b>3.34</b>	<b>2.00</b>
	129.40	130.40	1.00	1.16	714390		
FL15-33	134.00	134.50	0.50	8.59	714395		
	146.50	147.60	1.10	2.06	714409	<b>3.34</b>	<b>2.00</b>
147.60	148.50	0.90	0.92	714410			
FL15-34	9.00	10.00	1.00	2.32	714001	<b>7.09</b>	<b>2.00</b>
	10.00	11.00	1.00	11.85	714002		
FL15-34	26.30	26.90	0.60	83.30	714018	<b>21.90</b>	<b>2.40</b>
	26.90	27.90	1.00	0.30	714020		



	27.90	28.70	0.80	2.86	714021		
FL15-34	66.20	66.70	0.50	1.89	714063	<b>2.59</b>	<b>1.00</b>
	66.70	67.20	0.50	3.28	714064		
FL15-34	103.70	104.70	1.00	0.75	714105	<b>1.36</b>	<b>4.00</b>
	104.70	105.70	1.00	1.96	714106		
	105.70	106.70	1.00	1.62	714107		
	106.70	107.70	1.00	1.11	714108		
FL15-34	119.00	120.00	1.00	5.45	714120		
FL15-34	165.00	166.00	1.00	0.86	714172		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-34 Cont'd	166.00	167.00	1.00	0.47	714173	<b>1.95</b>	<b>17.00</b>
	167.00	167.90	0.90	0.88	714174		
	167.90	168.50	0.60	4.29	714176		
	168.50	169.50	1.00	2.18	714177		
	169.50	170.40	0.90	2.38	714178		
	170.40	171.10	0.70	2.32	714179		
	171.10	172.00	0.90	4.97	714181		
	172.00	173.00	1.00	2.53	714182		
	173.00	174.00	1.00	1.05	714183		
	174.00	175.00	1.00	2.61	714184		
	175.00	176.00	1.00	0.89	714185		
	176.00	177.00	1.00	0.45	714186		
	177.00	178.00	1.00	0.97	714187		
	178.00	179.00	1.00	0.91	714188		
	179.00	180.00	1.00	3.59	714189		
	180.00	181.00	1.00	4.39	714190		
181.00	182.00	1.00	0.58	714191			
FL15-34	202.00	203.00	1.00	3.88	714213		
FL15-34	227.00	228.00	1.00	0.51	714241		
FL15-35				NSR			
FL15-36	50.00	51.00	1.00	3.46	776551	<b>1.99</b>	<b>2.00</b>

	51.00	52.00	1.00	0.51	776552		
FL15-36	61.80	62.50	0.70	0.91	776564	<b>4.82</b>	<b>1.50</b>
	62.50	63.30	0.80	8.24	776565		
FL15-36	66.70	67.20	0.50	1.18	776570		
FL15-36	79.00	80.00	1.00	1.38	776585		
FL15-36	90.50	91.00	0.50	1.52	776596		
FL15-36	102.00	102.70	0.70	0.76	776609	<b>8.84</b>	<b>2.00</b>
	102.70	103.40	0.70	5.21	776610		
	103.40	104.00	0.60	22.50	776611		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-36	106.00	107.00	1.00	0.75	776615	<b>2.62</b>	<b>19.50</b>
	117.90	118.20	0.30	5.82	776629		
	122.00	122.80	0.80	4.70	776634		
	128.00	128.80	0.80	1.34	776641		
	128.80	129.50	0.70	2.22	776642		
	129.50	130.10	0.60	6.75	776643		
	130.10	130.70	0.60	1.65	776644		
	130.70	132.00	1.30	0.38	776645		
	132.00	133.00	1.00	0.35	776646		
	133.00	133.80	0.80	0.84	776647		
	133.80	134.70	0.90	10.50	776648		
	134.70	136.00	1.30	1.06	776649		
	136.00	136.60	0.60	0.09	776650		
	136.60	137.20	0.60	5.11	776651		
	137.20	137.80	0.60	16.35	776652		
	137.80	138.70	0.90	3.82	776653		
	138.70	139.40	0.70	0.50	776654		
	139.40	140.40	1.00	7.09	776655		
	140.40	140.90	0.50	0.09	776656		
	140.90	142.00	1.10	1.04	776657		
142.00	143.00	1.00	1.12	776658			

	143.00	144.00	1.00	0.73	776659		
	144.00	144.80	0.80	0.86	776661		
	144.80	146.00	1.20	0.71	776662		
	146.00	147.00	1.00	0.30	776663		
	147.00	147.50	0.50	4.87	776664		
FL15-36	163.00	164.00	1.00	2.73	776679		
FL15-37				NSR			
FL15-38	95.00	95.50	0.50	0.55	714497		
FL15-38	205.22	206.00	0.78	0.46	714612		
<b>HOLE-ID</b>	<b>FROM (m)</b>	<b>TO (m)</b>	<b>LENGTH (m)</b>	<b>Au (g/t)</b>	<b>SAMPLE</b>	<b>Wt. Avg. Au (g/t)</b>	<b>Interval (m)</b>
FL15-38	212.00	213.00	1.00	0.92	714619	<b>16.47</b>	<b>9.38</b>
	213.00	214.00	1.00	0.54	714621		
	214.00	214.75	0.75	0.78	714622		
	214.75	215.50	0.75	1.50	714623		
	215.50	216.13	0.63	7.26	714624		
	216.13	216.80	0.67	171.00	714626		
	216.80	218.00	1.20	1.07	714628		
	218.00	219.13	1.13	0.99	714629		
	219.13	219.80	0.67	23.10	714630		
	219.80	220.67	0.87	11.60	714631		
	220.67	221.38	0.71	5.90	714632		
FL15-38	237.00	237.57	0.57	1.40	714650		

NSR – no significant results

\* Drill Results highlighted and sub results use an cut-off grade of 0.40 g/t Au.

\*\* true width calculations indicate that core length is in excess of 90% of core length.

**Figure 1: Q2/15 Assay Hole Locations, Farley Lake Project, 2015 Feasibility Infill Drilling**

