

TABLE 1

Drill-Hole	Target Area	UTM-E (m)	UTM-N (m)	Elevation (m)	Azimuth (°)	Dip (°)	Total Length (m)	Intersection		Core Length (m)	Au g/t	Ag g/t	Cu %	Lithology
								From (m)	To (m)					
SST-01	Sub-Sill	422457.99	1989852.07	1152.97	315.00	-87.00	254.60	84.49	86.80	2.3	20.1	8.6	0.1	Skarn
								141.72	145.08	3.4	317.8	51.0	1.6	Skarn
								190.58	194.40	3.8	7.4	4.7	0.1	Skarn
SST-02	Sub-Sill	422424.19	1989818.21	1146.32	118	-55	236.5	70.52	77.00	6.5	7.2	1.1	0.0	Skarn
								101.65	105.08	3.4	12.1	47.6	5.5	Skarn
SST-03	Sub-Sill	422384.58	1989765.92	1138.39	99	-61	181.60	48.18	51.00	2.8	6.8	2.9	0.1	Skarn
SST-04	Sub-Sill	422384.67	1989884.13	1199.45	100	-82	329.50	320.76	322.95	2.2	1.4	19.0	0.7	Skarn
SST-05	Sub-Sill	422384.00	1989766.00	1138.00	279	-80	191.40	104.40	107.79	3.4	23.9	16.5	0.5	Skarn
SST-12	Sub-Sill	422326.72	1989842.02	1213.76	96	-82	283	186.77	190.31	3.5	8.7	1.0	0.0	Skarn
								205.20	213.83	8.6	8.0	8.2	0.3	Skarn
SST-13	Sub-Sill	422361.73	1989834.12	1192.23	90	-76	240.8	129.52	134.72	5.2	14.8	2.7	0.0	Skarn
								168.24	176.29	8.1	16.0	16.0	0.6	Skarn
SST-14	Sub-Sill	422448.44	1989828.48	1150.04	0	-90	158.5	67.53	73.93	6.4	7.0	8.8	0.2	Skarn
								83.71	91.75	8.0	12.5	3.6	0.1	Skarn
SST-19	Sub-Sill	422361.10	1989864.09	1205.91	0	-90	326.5	263.55	266.00	2.4	230.7	7.2	0.0	Skarn
								276.60	279.00	2.4	84.1	22.6	1.0	Skarn
SST-21	Sub-Sill	422425.03	1989864.50	1173.38	0	-90	230.60	39.56	41.12	1.6	1.3	3.0	0.1	Skarn
SST-22	Sub-Sill	422288.94	1989808.47	1204.86	90	-80	220.70	194.00	196.40	2.4	10.9	2.0	0.0	Skarn
SST-23	Sub-Sill	422284.75	1989808.71	1205.15	195	-85	309.30	No Intercepts						
SST-24	Sub-Sill	422337.85	1989794.80	1183.48	0	-90	336.10	155.14	158.30	3.2	3.9	3.5	0.0	Skarn
SST-25	Sub-Sill	422405.84	1989795.91	1142.97	0	-90	161.60	98.00	107.60	9.6	19.6	4.1	0.3	Skarn
SST-26	Sub-Sill	422336.05	1989794.12	1183.57	95	-76	191.50	158.12	160.00	1.9	42.8	6.0	0.0	Skarn
SST-27	Sub-Sill	422450.019	1989828.49	1150.34	90.00	-68.00	206.60	42.86	44.91	2.1	125.8	12.0	0.0	Skarn
								81.59	94.88	13.3	22.6	37.1	3.1	Skarn
SST-28	Sub-Sill	422458.66	1989852.00	1152.83	100	-70	180.00	90.76	95.61	4.8	8.6	17.2	0.6	Skarn
								104.53	111.56	7.0	14.9	45.6	1.5	Skarn
								127.55	128.56	1.0	103.2	123.0	3.4	Skarn
								136.50	139.82	3.3	17.3	23.4	0.9	Skarn
SST-29	Sub-Sill	422503.37	1989885.74	1160.24	0.00	-90.00	254.70	167.06	176.56	9.5	9.6	35.4	1.4	Skarn
								144.31	153.05	8.7	13.6	24.8	0.7	Skarn
SST-30	Sub-Sill	422504.40	1989887.29	1160.39	90	-70	239.50	137.46	138.92	1.5	50.4	23.7	0.3	Skarn
SST-32	Sub-Sill	422549.72	1989889.79	1163.20	130	-70	251.70	261.40	263.29	1.9	8.9	7.2	0.4	Skarn
SST-33	Sub-Sill	422286.63	1989760.58	1169.19	110	-70	367.00	292.07	293.86	1.8	11.2	8.2	0.4	Skarn
								54.68	58.95	4.3	83.3	18.1	1.1	Skarn
SST-34	Sub-Sill	422448.85	1989828.97	1150.32	90	-45	134.4	95.27	100.83	5.6	25.5	36.7	3.7	Skarn
								95.60	97.40	1.8	6.2	2.7	0.1	Skarn
SST-35	Sub-Sill	422558.82	1989851.56	1161.69	0	-90	161.70							

Notes:

True thickness of the mineralized zone is unknown and is reported as drill hole length

The gold values used to calculate the intercept composite are uncapped