

Table 2: Kunche - Final Infill Drilling Results (1m samples)

Hole ID	East	North	Depth (m)	Dip	Azimuth	From (m)	To (m)	Width (m)	Au (g/t)
KRCD551*	526823	1149625	192	-50	90	128.0	129.0	1.0	2.99
KRC552	526897	1148975	100	-50	90	96.0	98.0	2.0	1.61
KRC553	527070	1148873	70	-50	90	24.0	29.0	4.0	1.43
KRCD555*	526835	1149397	270	-50	90	0.0	1.0	1.0	1.16
						87.0	91.0	4.0	1.23
						146.0	147.0	1.0	1.90
KRCD556*	526996	1148700	220	-50	90	114.0	115.0	3.0	2.92
						128.0	129.0	1.0	1.29
KRCD557	526999	1148748	207	-50	90	156.1	161.8	5.7	1.44
						170.2	171.2	1.0	2.69
KRCD560*	526995	1148622	234	-50	90	147.8	148.6	0.8	1.10
						159.4	167.4	8.0	3.12
						173.4	174.4	1.0	1.83
						209.7	210.7	1.0	1.15
KRCD562	527090	1149572	270	-50	270	181.7	182.6	0.9	29.7
						219.8	220.4	0.6	1.06
						224.1	225.2	1.1	11.25
						231.8	236.9	5.1	1.95
						241.0	244.7	3.7	1.54
KRCD563	526846	1149499	220	-50	90	147.8	163.5	15.7	2.82
						193.2	194.7	1.5	1.80
						197.5	201.6	4.1	1.22
KRCD564*	526861	1149426	252	-50	90	143.7	146.2	2.5	1.49
						157.1	157.6	0.5	1.07
						182.0	184.0	2.0	2.57
						197.0	197.9	0.9	1.25
						200.5	203.0	2.5	2.29
						222.0	227.0	5.0	2.74
KRCD565	526992	1148725	210	-50	90	139.4	140.0	0.6	1.33
						189.6	190.7	1.1	2.36
KRCD567	526940	1149222	219	-50	90	84.0	85.0	1.0	2.50
						144.1	146.7	2.6	3.08
						154.9	162.2	7.4	2.01
						166.7	173.9	7.2	1.19
						178.5	189.1	10.6	2.15
KRCD572	526966	1148626	258	-50	90	175.3	177.4	2.1	1.95
						186.1	191.7	5.6	1.39
						195.8	196.8	1.0	2.48
						200.9	202.0	1.1	1.66
						207.2	208.2	1.0	1.10

Hole ID	East	North	Depth (m)	Dip	Azimuth	From (m)	To (m)	Width (m)	Au (g/t)
KRCD573	526995	1148902	183	-50	90	134.0	141.3	7.3	3.07
						145.8	150.0	4.2	1.17
KRCD574	526965	1149171	201	-50	90	112.0	113.0	1.0	19.70
						132.7	133.7	1.0	1.14
						140.0	141.0	1.0	1.39
						148.0	166.0	18.0	1.66
KRCD575	566871	1149324	272	-50	90	100.3	107.5	7.2	1.28
						123.0	126.0	3.0	2.60
						146.0	152.7	6.7	1.13
						169.0	169.8	0.8	8.70
						175.8	176.5	0.7	4.06
						192.0	193.0	1.0	1.05
						205.5	206.6	1.1	12.00
						214.0	215.0	1.0	1.39
						219.7	220.7	1.0	3.36
						227.0	236.1	9.1	2.53
						238.3	239.7	1.4	2.39
						251.2	253.0	1.8	3.24
KRCD576	526875	1149451	209	-50	90	126.4	127.4	1.0	1.84
						130.0	130.5	0.5	1.23
						138.0	139.0	1.0	3.90
						145.0	145.9	0.9	1.63
						151.0	151.8	0.8	1.66
						169.0	173.5	4.5	2.94
						176.0	181.5	5.5	4.85
						184.0	185.0	1.0	1.31

*Denotes an intercept previously reported as 4m composite intercept. Intercepts selected are based on a 1.0g/t gold lower cut-off (no upper-cut applied) and maximum 4m internal dilution. Widths are down-hole intervals. Sample analysed by 50gm Fire Assay method by SGS Takwa, Ghana, which has no relationship to Azumah. Drill hole collars are located by GPS with accuracy ± 5 m. The sampling procedures and analytical method (quality assurance and quality control programme) are consistent with those described in the NI43-101 Technical Report of Azumah Resources Limited, dated April 14, 2011