

Table 3: Bepkong - Final Infill Drilling Results (1m samples)

Hole ID	East	North	Depth (m)	Dip	Azimuth	From (m)	To (m)	Width (m)	Au (g/t)
BRCD302*	527023	1152225	204	-50	90	122.0	123.0	1.0	1.24
						126.4	127.6	1.2	3.20
						130.6	131.6	1.0	1.37
						140.4	141.4	1.0	1.47
						147.8	150.4	2.6	1.45
						153.4	154.4	1.0	1.28
						176.2	177.2	1.0	1.05
						195.0	196.0	1.0	11.1
						203.0	204.0	1.0	1.06
BRCD305	527023	1152174	220	-50	90	142.0	143.0	1.0	1.16
						180.0	184.0	4.0	1.13
						199.0	200.0	1.0	3.48

*Denotes an intercept previously reported as 4m composite intercept. Intercepts selected are based on a 1.0g/t gold lower cut-off (no upper-cut applied) and maximum 4m internal dilution. Widths are down-hole intervals. Sample analysed by 50gm Fire Assay method by SGS Takwa, Ghana, which has no relationship to Azumah. Drill hole collars are located by GPS with accuracy ± 5 m. The sampling procedures and analytical method (quality assurance and quality control programme) are consistent with those described in the NI43-101 Technical Report of Azumah Resources Limited, dated April 14, 2011