

Hole #	Section	Mineralized Zone	From (m)	To (m)	Interval (m)	Est. True Width (m)	Cu Eq (%)	Cu (%)	Ag (g/t)
South Limb South Diamond Drilling									
HA-388a-D includes	SL61850	South Limb South	156.34 159.88	178.96 162.44	22.62 2.56	19.23 2.18	0.41 2.12	0.37 2.00	3.00 8.00
HA-388b-D includes	SL61850	South Limb South	162.32 170.67 174.80	177.08 173.12 177.08	14.76 2.45 2.28	12.55 2.08 1.94	0.60 0.86 1.30	0.51 0.75 1.09	6.00 7.00 14.00
HA-389-D	SL58100	South Limb South	77.54	83.00	5.46	4.64	0.44	0.35	6.00
HA-390b-D includes	SL61650	South Limb South	209.00 216.00	220.83 220.83	11.83 4.83	10.06 4.11	1.14 2.60	0.92 2.08	15.00 36.00
HA-391-D includes	SL62025	South Limb South	170.31 177.00	180.86 180.00	10.55 3.00	8.97 2.55	0.63 1.11	0.54 0.95	6.00 11.00
HA-392-D includes	SL62025	South Limb South	159.92 163.70 197.15 204.84	170.50 170.50 213.00 211.37	10.58 6.80 15.85 6.53	8.99 5.78 13.47 5.55	0.77 1.12 0.56 1.09	0.68 1.01 0.45 0.87	6.00 8.00 7.00 15.00
HA-393-D includes	SL58300	South Limb South	49.00 57.70	60.70 60.05	11.70 2.35	9.95 2.00	0.93 3.57	0.74 2.74	13.00 57.00
HA-396-D includes	SL56725	South Limb South	47.50 57.12	60.88 60.19	13.38 3.07	11.37 2.61	0.79 2.20	0.66 1.81	9.00 27.00
HA-399-D includes	SL61650	South Limb South	168.65 169.96	173.66 173.33	5.01 3.37	4.26 2.86	2.14 3.06	1.71 2.44	29.00 42.00
HA-410b-D includes	SL61050	South Limb South	153.40 154.79	160.96 160.96	7.56 6.17	6.43 5.24	0.85 0.98	0.69 0.79	11.00 13.00

(1) Copper equivalent calculated using US\$3.00/lb Cu, US\$30/oz Ag and is not adjusted for metallurgical recoveries. The formula used is as follows: $CuEq = Cu\% + (Ag \text{ g/t} \times 0.01458)$.