

**Table 2: Details of Yellow Pine Drill Results, Golden Meadows Project**

*(To accompany Midas Gold news release #2013-16)*

HOLE ID	Hole Type	Collar Azimuth	Collar Dip	Hole Total Length (m)	From (m)	To (m)	Length (m) <sup>(1)</sup>	True Width (m) <sup>(2)</sup>	Gold (g/t)	Silver (g/t)	Antimony (%)	Tungsten (%)	Gold Equivalent <sub>-3</sub>
MGI-13-359	Core	120	-60	359.7	248.7	322	73.3	50	2.5	0.6	0.002	0.001	2.51
<i>including</i>					294.6	319.7	25.2	17	4.24	1	0.002	0.001	4.26
MGI-13-364	Core	175	-47	143.6	76.8	111.1	34.3	34.3	1.3	2.1	0.055	0.001	1.46
MGI-13-365	Core	192	-64	179.8	31.9	143.9	112	112	2.45	2.8	0.004	0.004	2.5
<i>including</i>					45.6	59.3	13.7	13.7	2.63	2.4	0.005	0.004	2.67
<i>including</i>					73	93.6	20.6	20.6	4.14	4.2	0.004	0.004	4.22
<i>and</i>					157.6	173.6	16	16	1.78	1.5	0.002	0.001	1.8
MGI-13-366	Core	192	-45	191.9	30.8	126.8	96	96	3.63	4.1	0.004	0.003	3.7
<i>including</i>					58.2	94.8	36.6	36.6	4.16	4.8	0.004	0.003	4.24
<i>including</i>					108.5	124.5	16	16	4.98	3.9	0.004	0.004	5.05
MGI-13-367	Core	279	-55	155.5	7.9	28.5	20.6	20.6	0.65	0.4	0.007	0.003	0.67
<i>and</i>					49.1	76.5	27.4	20	0.94	3.7	0.005	0.001	1
<i>and</i> <sup>(4)</sup>					111	155.5	44.5	44.5	1.64	6.9	0.63	0.001	3.26
MGI-13-368	Core	279	-38	158.8	7.2	43	35.8	35.8	1.48	19.9	1.09	0.002	4.41
<i>including</i>					25.5	36.9	11.4	11.4	3.08	27.2	2.309	0.002	9.05
<i>and</i> <sup>(4)</sup>					84.1	157.3	73.2	73.2	2.18	8	0.55	0.001	3.63
MGI-13-369	Core	235	-60	164.6	42.4	154.4	112	112	2.08	2	0.004	0.003	2.12
<i>including</i>					65.2	81.2	16	16	6.14	4.1	0.004	0.002	6.21
MGI-13-370	Core	315	-55	169.8	89.9	101.4	11.4	10	0.81	2	0.003	0.003	0.85
<i>and</i>					110.5	133.4	22.9	15	2.4	0.8	0.003	0.004	2.42
MGI-13-371	Core	333	-38	150	132.1	148.1	16	16	0.71	1	0.004	0.004	0.73
MGI-13-372 <sup>(4)</sup>	Core	315	-45	134.7	56.7	134.7	78	50	6.42	4.3	0.004	0.003	6.49
<i>including</i>					71.9	129.8	57.9	37	8.19	5.4	0.004	0.003	8.28
MGI-13-373 <sup>(5)</sup>	Core	309	-42	93.4	75.6	93.4	17.8	17.8	1.08	4	0.005	0.003	1.15
MGI-13-374	Core	278	-50	126.8	97.1	122.2	25.1	20	0.67	2.3	0.004	0.002	0.71
MGI-13-375 <sup>(4)</sup>	Core	290	-38	173.7	64.8	174	109.3	109.3	3.28	18.7	0.067	0.003	3.71
<i>including</i>					73.9	99.1	25.2	25.2	4.52	57.7	0.171	0.003	5.79
<i>including</i>					105.9	137.9	32	32	4.27	14.2	0.006	0.004	4.5
<i>including</i>					144.8	158.5	13.7	13.7	3.4	4.5	0.005	0.004	3.48
MGI-13-376 <sup>(4)</sup>	Core	350	-35	45.1	20.7	45.1	24.4	24.4	3.96	1.8	0.004	0.003	4
<i>including</i>					23	43.6	20.6	20.6	4.37	2	0.004	0.003	4.41
MGI-13-377 <sup>(5)</sup>	Core	65	-35	47.4	8.8	29.4	20.6	20.6	2.99	2.9	0.004	0.004	3.05

(1) Reported drill hole composites are reported at a 0.5 g/t Au cut-off, with a minimum 10 meter composite length. Higher grade composites are reported at 3 g/t Au cut-off. Composites may contain up to 6m of internal waste below cut-off.

(2) Estimated true widths.

(3) In situ gold equivalent values based on \$1,350/oz gold, \$20/oz Ag and \$4.75/lb antimony. These equivalent grades are provided for illustrative purposes only and do not account for recoveries or payabilities of the various metals, which may vary significantly, depending on the metallurgical process selected.

(4) Hole bottomed in mineralized.

(5) Hole did not reach planned depth.