

**Table II.** Underground drill hole results  $\geq 3$  g/t gold and  $\geq 0.2$  metres downhole.

Hole number	East	North	Dip (°)	Azimuth (°)	From (metres)	Width (metres)	Grade (uncut) (g/t gold)
<b><u>LEVEL 2</u></b>							
<b>L2-044</b>	613416	912949	0	322	3.80	0.60	11.17 (*)
<b>L2-047</b>	614057	913020	0	231	72.05	0.75	6.50 (*)
<b><u>LEVEL 4</u></b>							
<b>L4-023</b>	613922	912928	0	344	26.10	0.40	15.20 (*)
<b>L4-024</b>	613985	912881	0	152	108.55	2.40	24.34 (*)
<b>L4-025</b>	613982	912882	0	122	117.40	0.40	83.93 (*)
<b><u>LEVEL 5</u></b>							
<b>L5-067</b>	613945	912889	-58	138	60.45	0.80	5.87 (*)
					76.30	0.30	17.10 (*)
					251.10	0.40	11.37 (*)

**Notes:**

- (i) Intersection widths are downhole drill widths not true widths;
- (ii) Assays denoted by (\*) are by Philsaga Mining Corporation's laboratory, all other assays are by McPhar Geoservices Inc. in Manila;
- (iii) Grid co-ordinates based on the Philippine Reference System 92.