

GOLDEN RIDGE SIGNIFICANT DRILL INTERSECTIONS (PREVIOUS FREEWEST 1999 AND 2004 DRILL PROGRAMS)									
Hole No.	Easting	Northing	Azimuth	Dip		From (metres)	To (metres)	Interval (metres) 1	Au (g/t) 2
GR-99-02	2400650	7433139	295°	-45°		76.50	80.40	3.90	1.28
						91.60	103.60	<b>12.00</b>	<b>1.58</b>
					including	92.60	96.30	3.70	4.03
GR-99-05	2400555	7433195	115°	-45°		35.60	61.00	<b>25.40</b>	<b>1.09</b>
					including	36.80	50.70	<b>13.90</b>	<b>1.48</b>
						67.00	79.50	12.50	0.77
GR-99-06	2400358	7433116	115°	-45°		86.30	110.00	<b>23.70</b>	<b>0.78</b>
					including	87.7	90.40	2.70	2.03
					and	106.80	110.00	3.20	2.39
GR-99-07	2400337	7433013	115°	-45°		23.50	44.00	20.50	0.44
					including	29.10	31.60	2.50	1.34
GR-99-08	2400220	7433300	295°	-45°		21.00	48.70	<b>27.70</b>	<b>0.47</b>
					including	22.30	24.60	2.30	1.21
GR-99-10	2400522	7433220	110°	-60°		62.60	78.30	<b>15.70</b>	<b>1.47</b>
					including	69.60	74.10	4.50	2.12
						136.00	149.40	<b>13.40</b>	<b>2.54</b>
				including	143.10	149.40	<b>6.30</b>	<b>4.55</b>	
GR-04-11	2400532	7433214	112°	-50°		68.10	117.00	<b>48.90</b>	<b>1.47</b>
					including	84.60	117.00	32.40	1.91
GR-04-12	2400500	7433232	112°	-64.5°		8.00	32.00	<b>24.00</b>	<b>1.03</b>
					including	8.00	16.00	8.00	1.68
					and	26.25	32.00	5.75	1.70
						61.85	65.50	3.65	1.89
					261.15	268.36	7.21	0.53	
GR-04-13	2400586	7433184	112°	-45°		15.00	60.36	<b>45.36</b>	<b>0.90</b>
					including	18.23	30.00	11.77	1.26
					and	37.00	48.00	11.00	1.20
					and	54.00	59.00	5.00	1.52
GR-04-14	2400582	7433126	112°	-45°		15.80	63.00	<b>47.20</b>	<b>1.08</b>
					including	15.80	19.22	3.42	3.32
					and	40.36	48.28	7.92	1.84
					and	53.00	63.00	10.00	1.29
GR-04-15	2400560	7433136	112°	-45°		49.30	79.75	<b>30.45</b>	<b>1.49</b>
					including	49.30	52.60	3.30	3.04
					and	67.70	74.00	6.30	2.06
GR-04-16	2400542	7433150	112°	-48°		74.08	131.30	<b>57.22</b>	<b>0.55</b>
					including	74.08	77.50	3.42	1.95
					and	119.00	122.20	3.20	2.45
GR-04-17	2400603	7433166	117°	-45°		8.00	26.75	<b>18.75</b>	<b>1.22</b>
					including	12.40	17.05	4.65	2.55

<sup>1</sup>Intervals are core length. True width will be defined with additional drilling

<sup>2</sup> Rockport assays performed by Activation Laboratories Ltd, Ontario using the fire assay method (A3-50) on 50 grams of prepared sample and/or INAA (1H (Au+48)). All INAA assay results > than 500 ppb gold have been also analyzed using the fire assay method. Previous Freewest assays performed by Activation Laboratories using INAA (Au +34; 1D)